



UNDERSTANDING POTENTIAL- INDUCED DEGRADATION (PID) OF PHOTOVOLTAIC (PV) MODULES

DR MAHMOUD DHIMISH
UNIVERSITY OF YORK, UK

PEARL PV'S TRAINING
SCHOOL ON THE POTENTIAL
OF MONITORING TOOLS AND
ADVANCED OPERATION AND
MAINTENANCE PRACTICE
FOR SECURITY AND
PREDICTABILITY OF PV
PERFORMANCE

CONTENTS



Myself!



What is PID?



PID AFFECT!



PID Recovery/Mitigation



PID defects acceleration and correlation



Conclusions



Questions

DR. MAHMOUD DHIMISH

- **Sept. 2021 - present:** Lecturer (Assistant Professor) in Electrical Engineering, Department of Electronic Engineering, University of York.
- **May. 2018 – August 2021:** Lecturer/Senior Lecturer in Electronics and Control Engineering, School of Computing and Engineering, University of Huddersfield.
- **Jan. 2016 – Dec. 2016:** Research Assistant, project title: “PV output power enhancement using new intelligent PV configurations”. School of Electronic and Electrical Engineering, Leeds University.



Contact details


Type of address	Postal address
Postal code	YO10 5DD
Country/Territory	United Kingdom
Address lines	Electronic Engineering University of York Heslington York YO10 5DD
Phone:	(01904) 323892
	mahmoud.dhimish@york.ac.uk

WHAT IS PID?

PID stands for potential induced degradation.


PID occurs because of minor, unwanted currents between the semiconductor on the one side, and the glass, **anti-reflective coating (ARC)**, the frame, and the mounting on the other side.

The degradation in performance is associated with migration of **sodium ions**, from the glass plate through the encapsulation (commonly: EVA) and the Anti-Reflective Coating (ARC) to the cell.



**higher
negative
potential**



sodium ions?



PID does not occur in grounded systems where the negative pole of the inverter is grounded

PID & INVERTER


[What is PID and how can you reduce solar power loss? – HSB Equipment Connection Blog](#)



In the case of an ungrounded system the PID effect is most severe in the modules with the highest negative potential

PID & INVERTER

[What is PID and how can you reduce solar power loss? – HSB Equipment Connection Blog](#)





PID EFFECT

TESTING PROCEDURE - INDOOR


80% relative humidity, 85°C and biased with a voltage of -
1000 V, for 96 hours



PV Module




**ELECTROLUM
INESCENCE
(EL) IMAGING**




MONOCRYSTALLINE SILICON PHOTOVOLTAIC – CASE STUDY



Dhimish, M., & Tyrrell, A. M. (2022).
Monocrystalline silicon photovoltaic
mitigation of potential-induced degradation
using SiO₂ thin film and+ 1000 V
biasing. *Optik*, 168732.





MONOCRYSTALLINE
SILICON
PHOTOVOLTAIC -
CASE STUDY



MONOCRYSTALLINE SILICON PHOTOVOLTAIC – CASE STUDY





MONOCRYSTALLINE SILICON PHOTOVOLTAIC – CASE STUDY




approximate increase in temperature from 25°C to 45°C.

MONOCRYSTALLINE SILICON PHOTOVOLTAIC – CASE STUDY




FIELD CASE STUDY

Dhimish, M., & Tyrrell, A. M. (2022). Power loss and hotspot analysis for photovoltaic modules affected by potential induced degradation. *npj Materials Degradation*, 6(1), 1-8.



FIELD CASE STUDY

Dhimish, M., & Tyrrell, A. M. (2022). Power loss and hotspot analysis for photovoltaic modules affected by potential induced degradation. *npj Materials Degradation*, 6(1), 1-8.




FIELD CASE STUDY

Dhimish, M., & Tyrrell, A. M. (2022). Power loss and hotspot analysis for photovoltaic modules affected by potential induced degradation. *npj Materials Degradation*, 6(1), 1-8.




$$PR = \frac{P_{MEASURED}}{P_{STC} \frac{G_{poa}}{G_{ref}} (1 + \gamma (T_{PV} - T_{ref}))}$$



FIELD CASE STUDY


Dhimish, M., & Tyrrell, A. M. (2022). Power loss and hotspot analysis for photovoltaic modules affected by potential induced degradation. *npj Materials Degradation*, 6(1), 1-8.



The mean value of the PV modules temperature varies between 25°C to 42°C.



INDUSTRIAL EXAMPLE

Dhimish, M., & Tyrrell, A. M. (2022). Filed Study on the Severity of Photovoltaic Potential Induced Degradation. *IEEE Open Journal of Instrumentation and Measurement*.



INDUSTRIAL EXAMPLE

Dhimish, M., & Tyrrell, A. M. (2022). Filed Study on the Severity of Photovoltaic Potential Induced Degradation. *IEEE Open Journal of Instrumentation and Measurement*.




INDUSTRIAL EXAMPLE

Dhimish, M., & Tyrrell, A. M. (2022). Filed Study on the Severity of Photovoltaic Potential Induced Degradation. *IEEE Open Journal of Instrumentation and Measurement*.

PV String	PR (first month) (%)	PR (after 12-months) (%)	Difference (%)
1	96.5	56.6	39.9
2	94.8	58.3	36.5
3	96.1	66.9	29.2
4	96.3	68.4	27.9
5 (Healthy string)	95.7	94.4	0.3


INDUSTRIAL EXAMPLE

Dhimish, M., & Tyrrell, A. M. (2022). Filed Study on the Severity of Photovoltaic Potential Induced Degradation. *IEEE Open Journal of Instrumentation and Measurement*.



INDUSTRIAL EXAMPLE

Dhimish, M., & Tyrrell, A. M. (2022). Filed Study on the Severity of Photovoltaic Potential Induced Degradation. *IEEE Open Journal of Instrumentation and Measurement*.



Sky image for the PV operation condition. a Clear sky. **b** Partial shading. **c** Overcasting. These images were taken using TSI 440A total sky imager. The temperature of the PV modules at these conditions is 26°C, 23°C and 19°C, respectively; and the solar radiation is 730 W/m², 677 W/m², and 408 W/m².

PV Modules	Environment Condition: Clear Sky (26°C, 730 W/m ²)				
	V _{OC} (V)	I _{SC} (A)	V _{MPP} (V)	I _{MPP} (A)	P _{MPP} (W)
Healthy	183.6	8.1	143.9	7.66	1102
PID	134.1	8.0	90.3	7.67	692.6
Difference* (%)	-26.9	-1.23	-37.2	+0.13	-37.15

PV Modules	Environment Condition: Partial Shading (23°C, 677 W/m ²)				
	V _{OC} (V)	I _{SC} (A)	V _{MPP} (V)	I _{MPP} (A)	P _{MPP} (W)
Healthy	183.1	8.1	145.8	7.33	1069
PID	133.6	7.9	90.9	7.49	681.0
Difference* (%)	-27.0	-2.47	-37.6	+2.18	-36.29


PV Modules	Environment Condition: Overcasting (19°C, 408 W/m ²)				
	V _{OC} (V)	I _{SC} (A)	V _{MPP} (V)	I _{MPP} (A)	P _{MPP} (W)
Healthy	181.8	8.1	155.3	5.62	872.6
PID	130.8	7.9	102.4	5.14	526.2
Difference* (%)	-28.1	-2.47	-34.06	-8.54	-39.69

*The "difference" is calculated as the following: $\left[100 - \left(\frac{\text{PID electrical parameter}}{\text{Healthy electrical parameter}} \times 100\right)\right]$. The negative sign explains how much loss in the relevant electrical parameter is induced due to the presence of PID.

PID RECOVERY

PID RECOVERY


Dhimish, M., & Badran, G. (2021). Recovery of Photovoltaic Potential-Induced Degradation Utilizing Automatic Indirect Voltage Source. *IEEE Transactions on Instrumentation and Measurement*.



Automatic
Indirect
Voltage Source
+1000 V


PID RECOVERY

Dhimish, M., & Badran, G. (2021). Recovery of Photovoltaic Potential-Induced Degradation Utilizing Automatic Indirect Voltage Source. *IEEE Transactions on Instrumentation and Measurement*.




PID RECOVERY

Dhimish, M., & Badran, G. (2021).
Recovery of Photovoltaic Potential-
Induced Degradation Utilizing Automatic
Indirect Voltage Source. *IEEE
Transactions on Instrumentation and
Measurement*.




DAY 9




PID RECOVERY

Dhimish, M., & Badran, G. (2021). Recovery of Photovoltaic Potential-Induced Degradation Utilizing Automatic Indirect Voltage Source. *IEEE Transactions on Instrumentation and Measurement*.




PID RECOVERY

Dhimish, M., & Badran, G. (2021). Recovery of Photovoltaic Potential-Induced Degradation Utilizing Automatic Indirect Voltage Source. *IEEE Transactions on Instrumentation and Measurement*.




PID RECOVERY-ARC

Dhimish, M., & Tyrrell, A. M. (2022). Monocrystalline silicon photovoltaic mitigation of potential-induced degradation using SiO₂ thin film and+ 1000 V biasing. *Optik*, 168732.




No SiO₂ thin film layer (First Module)



Contain SiO₂ thin film layer (Second Module)


PID RECOVERY-ARC

Dhimish, M., & Tyrrell, A. M. (2022). Monocrystalline silicon photovoltaic mitigation of potential-induced degradation using SiO₂ thin film and+ 1000 V biasing. *Optik*, 168732.




PID RECOVERY-ARC


Dhimish, M., & Tyrrell, A. M. (2022). Monocrystalline silicon photovoltaic mitigation of potential-induced degradation using SiO₂ thin film and+ 1000 V biasing. *Optik*, 168732.



No SiO₂ thin film layer (First Module)



Contain SiO₂ thin film layer (Second Module)







PID DEFECTS ACCELERATION AND CORRELATION



IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS

Dhimish, M., & Kettle, J. (2021). Impact of Solar Cell Cracks Caused During Potential-Induced Degradation (PID) Tests. *IEEE Transactions on Electron Devices*, 69(2), 604-612.




IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS

Dhimish, M., & Kettle, J. (2021). Impact of Solar Cell Cracks Caused During Potential-Induced Degradation (PID) Tests. *IEEE Transactions on Electron Devices*, 69(2), 604-612.



IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS



Dhimish, M., & Kettle, J. (2021). Impact of Solar Cell Cracks Caused During Potential-Induced Degradation (PID) Tests. *IEEE Transactions on Electron Devices*, 69(2), 604-612.



“By inspection of the busbar’s metallic (solder) joint to the solar cell surface, it is evident that the solder has migrated and deformed around the solder joint.”

IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS


Dhimish, M., & Kettle, J. (2021). Impact of Solar Cell Cracks Caused During Potential-Induced Degradation (PID) Tests. *IEEE Transactions on Electron Devices*, 69(2), 604-612.



IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS



Dhimish, M., & Lazaridis, P. I. (2021). An empirical investigation on the correlation between solar cell cracks and hotspots. *Scientific reports*, 11(1), 1-11.

(a) mode 1, (b) mode 2, (c) mode 3, and (d) mode 4.





IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS

Dhimish, M., & Lazaridis, P. I. (2021). An empirical investigation on the correlation between solar cell cracks and hotspots. *Scientific reports*, 11(1), 1-11.




IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS

Dhimish, M., & Lazaridis, P. I. (2021). An empirical investigation on the correlation between solar cell cracks and hotspots. *Scientific reports*, 11(1), 1-11.



IMPACT OF SOLAR CELL CRACKS CAUSED DURING POTENTIAL INDUCED DEGRADATION (PID) TESTS

Dhimish, M., & Lazaridis, P. I. (2021). An empirical investigation on the correlation between solar cell cracks and hotspots. *Scientific reports*, 11(1), 1-11.



CONCLUSION!

We are still have limited knowledge of the impact of PID! we need more case studies and long-term field analysis!

What is the actual correlation between cracks, PID, hotspots, and other mismatching PV conditions!



QUESTIONS!

**CONSTRUCTIVE
DISCUSSION!**

